



# SaleroLED



## LED SLIM AREA LIGHT

### PRODUCT DESCRIPTION:

SaleroLED SPRK Series LED slim area lights are perfect replacements for up to 1000 watts HPS and existing metal halide area lighting. They feature a low profile and high efficiency LED driver, high lumens and long life Phillips Lumileds LED chips. Light utilization and uniformity are improved immensely with the excellent optical design.

SaleroLED SPRK series also features a cast aluminum design which provides better cooling and a low maintenance solution for lighting.

### APPLICATIONS:

- Urban roads
- Industrial areas
- Residential areas
- Sidewalks
- Parking lots

### FEATURES:

- Slim and low profile design
- Photocell and Shorting Cap optional
- Wet location and IP65 rated
- >50,000 hours rate life
- Chip: Philips Lumileds LED
- Luminous Flux: 39,000LM
- Light Efficiency: 130LM/W
- Fixture Size: 23 x 12.5 x 3.3 in
- Weight: 19.84 lbs
- UL LED driver PF>0.95, THD<10%, with 10KV surge protection
- Qualified with CE, RoHS, cETL, ETL, DLC Premium
- LM-79/80 data available
- Ambient temperature from -40°F to 104°F
- 5-Year Warranty

**DLC V4.4**



MODEL # SPRK-300 - Shown without available photocells.



MODEL # SPRK-300 - Shown with available photocells/shorting cap.



Three mounting options: Yoke, Slip Fit and Universal Direct Mount (Direct Mount compatible with round or square poles)

Model No.	Power	CCT	Voltage	Type	Control	Mount
SPRK-	300W	50 = 5000K	UNV = AC120 - 277V	3 = III 4 = IV† 5 = V†	Blank = None PC = Twist Lock Photocell SC = Twist Lock Shorting Cap	YK = Yoke SF = Slip Fit DM = Direct Mount (round or square pole)
				† MTO (Made to Order)		

Example order syntax: **SPRK - 300W - 50 - UNV - 3 - PC - SF**

|     /     /     /     /     /     /  
 Model Power CCT Voltage Type Control Mount